




ER910/920 Series Cardiac Event Monitors



Braemar, Inc.

Superior Ambulatory Monitoring with Atrial Fibrillation and Arrhythmia Detection Algorithms

- Diagnostic Embedded Algorithms that Automatically Trigger Recordings Of Asymptomatic Events
 - Including Atrial Fibrillation, Brady Arrhythmia, Tachy Arrhythmia and Cardiac Pause
- Large Single Button Operation for Symptomatic Event Recording and Transmission of Event
- Large LCD Display
 - Confirms Device Operation
 - Confirms Battery Life
 - Confirms Number of Events Remaining
- Field Upgradeable Firmware
- 30 Minute Programmable Looping Memory
- > 30 Days of Battery Life with Two AAA Batteries with Arrhythmia Algorithm On
 - Reduces Cost of Ownership
- Pacemaker Detection
- Lead Loss Detection
- 1x or 3x for Data Transmission or Direct Upload via Serial Port
- Simple Patient Operation with One Button Record and Send

The Braemar ER910/920 Cardiac Event Monitors are the world's most advanced, with superior technology providing the documentation of symptomatic and asymptomatic cardiac events.

The simple single button operation allows patients to document and record symptomatic transient cardiac events; including syncope, palpitations, dizziness, chest discomfort and shortness of breath.

The Braemar ER910/920 Series Cardiac Event Monitors enhance diagnostic yield further with embedded algorithms that automatically trigger recordings of asymptomatic events such as atrial fibrillation, bradycardia, tachycardia and cardiac pause.

ER910/920 Series Cardiac Event Monitors

Product Specifications

FUNCTIONAL

Channels
 ER910.....1
 ER920.....2
 Number of Events.....1-30
 Functional Recording Time....256 Samples Per Second

MEMORY

Total Recording Time.....30 Minutes (1800 sec)
 Maximum Event Time
 One Channel5 Minutes (300 sec)
 Two Channel.....5 Minutes (300 sec)
 Type.....Flash
 Data Retention.....10 Years Minimum

PHYSICAL

Dimensions.....3.5" x 2.125" x .65"
 (90mm x 54mm x 16mm)
 Weight with Batteries.....3.5 oz

TRANSMISSION CHARACTERISTICS

Transmission possible via telephone (ttm connect)
 or by direct connect to PC via Serial Port

Direct Serial Port Upload

Transmission ModeRS232, PC Serial Port
 Transmission Rate.....11500 Baud

ENVIRONMENTAL

Operating Temperature.....0°C (32°F) to 45°C (113°F)
 Non-operating Temperature...-20°C (-4°F) to 65°C (149°F)
 Operating Humidity.....10% to 95% (Non-condensing)
 Non-operating Humidity.....5% to 95% (Non-condensing)

BATTERY

Type.....(2) AAA Alkaline IEC-LR3
 Life.....1 Month



ER 910



ER 920


PROGRAMMABLE OPTIONS

- Pre-Event Time 5-285 seconds
- Post-Event Recording Time: 5-285 seconds
- Number of Events
- Audible or Silent Operation
- Audible Feedback
- ECG Signal Preview Time
- Display Information
- Number of Channels (ER920)
- Pacemaker Detection ON/OFF
- Lead Loss ON/OFF
- 1x/3x Transmission Rate
- Auto Detection ON/OFF
- Bradycardia, Tachycardia and Pause Settings
- Atrial Fibrillation

ELECTRICAL

Input Impedance..... 10 Mohms Minimum
 CMRR..... 70 dB Minimum
 AC Signal Range +/- 3mV
 DC Signal Range..... +/- 300mV
 Resolution..... 8 bit
 Frequency Response 0.05Hz to 40Hz

WARRANTY..... 1 Year
 Made in USA



Braemar, Inc.

1285 Corporate Center Drive
 Suite 150
 Eagan, MN 55121 USA

Jason Blades
 Managing Director
 Innovative Medical Solutions

Unit 8, 9 Merino Entrance
 COCKBURN CENTRAL
 WESTERN AUSTRALIA, 6164

Postal: PO Box 5008, SOUTH LAKE, W.A., 6164
 info@innovativemedical.com.au
 www.innovativemedical.com.au

Phone: 1300 884 612
 Fax: 1300 884 613
 Mobile: 0411 177 795

